



Mainline Metals and Mainline Processing Overview

Established in 1986, Mainline Metals' focus is on large quantities of prime, excess and secondary flat rolled steel products.

We maintain an extensive inventory at our full line service center in Blytheville, AR and at strategic locations throughout the country.

Mainline Metals carries all flat rolled products including HR, HRPO, CR, CRFH and all coated products.

Mainline processing is ISO 9001 : 2008 certified and can handle any of your processing needs.

Corporate Office:

Mainline Metals, Inc.
21 Bala Avenue
Bala Cynwyd, PA 19004
Phone: 610-668-0888
Toll Free: 800-355-0888
Fax: 610-668-1790
Web: www.mainlinemetals.com

Processing Facility:

Mainline Processing, Inc.
5550 E. State Hwy 137
Blytheville, AR 72315
Phone: 870-763-3000
Fax: 870-763-3008

Plant Information

Building Size: 45,000 square feet (75' x 600')

Land: 20 Acres

Processing Equipment:

- Loopco 50,000 lb. capacity x 60" wide slitter (.010 - .180 gauge range)
- Delta 45,000 lb. capacity x 60" wide slitter (.020 - .115 gauge range)
- Crane: 30 Ton Deshazio

Mainline Processing Inc.

Mainline Processing, Inc.
5550 E. State Hwy 137

LOOPCO 50,000 LBS CAPACITY X 60" WIDE SLITTER

General Specifications

Material Gauge Range	.010"-.1875"
Maximum Entry Width	62"
Maximum Slit Width	60"
Entry Coil ID	20"-24"
Exit Coil ID	20" (24" ID in 90 Days)
Max Yield Strength	Full Hard
Line Direction	Left to Right

Slit Cut Capacity

Low Speed Range (Pull Through & Helper):

- 6 Cuts in 0.180" Thick @ 320 FPM
- 8 Cuts in 0.150" Thick @ 320 FPM
- 12 Cuts in 0.120" Thick @ 380 FPM
- 16 Cuts in 0.090" Thick @ 450 FPM
- 18 Cuts in 0.075" Thick @ 600 FPM
- 25 Cuts in 0.060" Thick & Lighter @ 1200 FPM Max

High Speed Range:

- 6 Cuts in 0.120" Thick @ 800 FPM
- 8 Cuts in 0.150" Thick @ 800 FPM
- 11 Cuts in 0.090" Thick @ 800 FPM
- 16 Cuts in 0.075" Thick @ 800 FPM
- 25 Cuts in 0.060" Thick @ 900 FPM
- 25 Cuts in 0.048" Thick @ 1200 FPM
- 25 Cuts in 0.036" & Lighter @ 1200 FPM Max

Free Loop Drive Slitting (High Speed Range):

- 10 Cuts in 0.036" Thick @ 800 FPM
- 15 Cuts in 0.030" Thick @ 800 FPM
- 20 Cuts in 0.025" Thick @ 800 FPM

Mainline Processing Inc.

Mainline Processing, Inc.
5550 E. State Hwy 137

DELTA 45,000 LBS CAPACITY X 60" WIDE SLITTER

General Specifications

Material Gauge Range	.010"-.1875"
Maximum Entry Width	62"
Maximum Slit Width	60"
Entry Coil ID	20"-24"
Exit Coil ID	20" (24" ID in 90 Days)
Max Yield Strength	50,000 PSI
Line Direction	Left to Right

Slit Cut Capacity

High Speed Range (Based on 3 to 1 Build Up):

- 14 Cuts in 0.078" Thick @ 300 - 900 FPM
- 20 Cuts in 0.063" Thick @ 300 - 900 FPM
- 20 Cuts in 0.048" Thick @ 300 - 900 FPM
- 20 Cuts in 0.035" Thick @ 300 - 900 FPM
- 20 Cuts in 0.024" Thick @ 300 - 900 FPM
- 20 Cuts in 0.020" Thick @ 300 - 900 FPM